

NEMA 3R Vented Enclosures with Disconnect



SCE-47XVR2514 Vented Type 3R Disconnect Enclosure - 47" H X 25.38" W X 14" D

The SCE-47XVR2514 is a 47 x 25.38 x 14 Vented Type 3R Disconnect Enclosure from Saginaw Control & Engineering. Each SCE-47XVR2514 measures 47 Inches High X 25.38 Inches Wide X 14 Inches Deep. This SCE-47XVR2514 is Rated / Listed: NEMA 3R, UL Listed Type 3R, CSA Type 3R, IEC 60529, IP 66. Each Saginaw Control SCE-47XVR2514 Vented Type 3R Disconnect Enclosure weighs 215 lbs.

SCE-47XVR2514 Vented Type 3R Disconnect Enclosure Application: Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

SCE-47XVR2514 Dimensions: 47 x 25.38 x 14

SCE-47XVR2514 Finish: White powder coating inside and out. Optional sub-panels are powder coated white.

Notes:

Because the SCE-47XVR2514 units are Made in the USA by Saginaw Control with 100% US components, the SCE-47XVR2514 from SCE meets all requirements of ARRA and Buy America. Every SCE-47XVR2514 has the highest quality and American craftsmanship built in.

Most of all, the SCE-47XVR2514 Vented Type 3R Disconnect Enclosure comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-47XVR2514 Vented Type 3R Disconnect Enclosure units are rated for NEMA 3R environment and therefore have an Industry Standard of IS7. Each SCE-47XVR2514 Vented Type 3R Disconnect Enclosure is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom Vented Type 3R Disconnect Enclosure. If this Vented Type 3R Disconnect Enclosure or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

Recommended Accessory / Subpanel

[SCE-42P24](#)

Data Sheet

[SCE-47XVR2514 Datasheet / Cutsheet](#)

Drawing / CAD Files

[SCE-47XVR2514 Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x_t files\)](#)

Installation Information

[SCE-47XVR2514 Installation Information](#)

Manufacturer Page

[SCE-47XVR2514 Manufacturer Page](#)

SCE-47XVR2514 Notes

SCE-47XVR2514 Application

Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

~~\$1,217.47~~ **\$898.61 You Save Today!** (SCE-47XVR2514)



SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect - 53" H X 37.38" W X 16" D

The SCE-53XVR3716 is a 53 x 37.38 x 16 Enclosure, Vented Type 3R Disconnect from Saginaw Control & Engineering. Each SCE-53XVR3716 measures 53 Inches High X 37.38 Inches Wide X 16 Inches Deep. This SCE-53XVR3716 is Rated / Listed: NEMA 3R, UL Listed Type 3R, CSA Type 3R, IEC 60529, IP 66. Each Saginaw Control SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect weighs 235 lbs.

SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect Application: Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

SCE-53XVR3716 Dimensions: 53 x 37.38 x 16

SCE-53XVR3716 Finish: White powder coating inside and out. Optional sub-panels are powder coated white.

Notes:

Because the SCE-53XVR3716 units are Made in the USA by Saginaw Control with 100% US components, the SCE-53XVR3716 from SCE meets all requirements of ARRA and Buy America. Every SCE-53XVR3716 has the highest quality and American craftsmanship built in.

Most of all, the SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect units are rated for NEMA 3R environment and therefore have an Industry Standard of IS7. Each SCE-53XVR3716 Enclosure, Vented Type 3R Disconnect is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom Enclosure, Vented Type 3R Disconnect. If this Enclosure, Vented Type 3R Disconnect or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

Recommended Accessory / Subpanel

[SCE-48P36](#)

Data Sheet

[SCE-53XVR3716 Datasheet / Cutsheet](#)

Drawing / CAD Files

[SCE-53XVR3716 Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x_t files\)](#)

Installation Information

[SCE-53XVR3716 Installation Information](#)

Manufacturer Page

[SCE-53XVR3716 Manufacturer Page](#)

SCE-53XVR3716 Notes

SCE-53XVR3716 Application

Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

~~\$1,852.57~~ **\$1,367.38** **You Save Today!** (SCE-53XVR3716)



SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect - 65" H X 37.38" W X 16" D

The SCE-65XVR3716 is a 65 x 37.38 x 16 Enclosure, Vented Type 3R Disconnect from Saginaw Control & Engineering. Each SCE-65XVR3716 measures 65 Inches High X 37.38 Inches Wide X 16 Inches Deep. This SCE-65XVR3716 is Rated / Listed: NEMA 3R, UL Listed Type 3R, CSA Type 3R, IEC 60529, IP 66. Each Saginaw Control SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect weighs 277.67 lbs.

SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect Application: Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

SCE-65XVR3716 Dimensions: 65 x 37.38 x 16

SCE-65XVR3716 Finish: White powder coating inside and out. Optional sub-panels are powder coated white.

Notes:

Because the SCE-65XVR3716 units are Made in the USA by Saginaw Control with 100% US components, the SCE-65XVR3716 from SCE meets all requirements of ARRA and Buy America. Every SCE-65XVR3716 has the highest quality and American craftsmanship built in.

Most of all, the SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect units are rated for NEMA 3R environment and therefore have an Industry Standard of IS7. Each SCE-65XVR3716 Enclosure, Vented Type 3R Disconnect is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom Enclosure, Vented Type 3R Disconnect. If this Enclosure, Vented Type 3R Disconnect or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

Recommended Accessory / Subpanel

[SCE-60P36](#)

Data Sheet

[SCE-65XVR3716 Datasheet / Cutsheet](#)

Drawing / CAD Files

[SCE-65XVR3716 Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x_t files\)](#)

Installation Information

[SCE-65XVR3716 Installation Information](#)

Manufacturer Page

[SCE-65XVR3716 Manufacturer Page](#)

SCE-65XVR3716 Notes

SCE-65XVR3716 Application

Designed to house electrical controls, drives, instruments and components used in an outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). Designed to house most standard disconnects.

~~\$2,073.52~~ **\$1,530.47 You Save Today!** (SCE-65XVR3716)