

## Stainless Steel Heavy Duty Four Door Enclosures for Flange Mounted Disconnects



### SCE-84XM4EW18SS 4DR XM Enclosure - 84" H X 157.5" W X 18"

The SCE-84XM4EW18SS is a 84 x 157.5 x 18 4DR XM Enclosure from Saginaw Control & Engineering. Each SCE-84XM4EW18SS measures 84 Inches High X 157.5 Inches Wide X 18 Inches Deep. This SCE-84XM4EW18SS is Rated / Listed: NEMA 3R, NEMA 12, NEMA 13, UL Listed Type 3R, UL Listed Type 12, CSA Type 3R, CSA Type 12, IEC 60529, IP 55. Each Saginaw Control SCE-84XM4EW18SS 4DR XM Enclosure weighs 1850 lbs.

SCE-84XM4EW18SS 4DR XM Enclosure Application: Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

SCE-84XM4EW18SS Dimensions: 84 x 157.5 x 18

SCE-84XM4EW18SS Finish: 304 Stainless Steel. #4 brushed finish on all exterior surfaces. Sub-panels are powder coated white.

Notes: Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Because the SCE-84XM4EW18SS units are Made in the USA by Saginaw Control with 100% US components, the SCE-84XM4EW18SS from SCE meets all requirements of ARRA and Buy America. Every SCE-84XM4EW18SS has the highest quality and American craftsmanship built in.

Most of all, the SCE-84XM4EW18SS 4DR XM Enclosure comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-84XM4EW18SS 4DR XM Enclosure units are rated for NEMA 3R, 12, 13 environment and therefore have an Industry Standard of IS3. Each SCE-84XM4EW18SS 4DR XM Enclosure is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom 4DR XM Enclosure. If this 4DR XM Enclosure or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

### Included Accessories

[SCE-76P76](#) SCE-76P76 Subpanel, Bent  
Quantity 2 included with enclosure. Replacement plates can be ordered.

### Recommended Accessory / Subpanel

[SCE-13ELJEXPP](#)

### Data Sheet

[SCE-84XM4EW18SS Datasheet / Cutsheet](#)

### Drawing / CAD Files

[SCE-84XM4EW18SS Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x\\_t files\)](#)

### Installation Information

[SCE-84XM4EW18SS Installation Information](#)

### Manufacturer Page

[SCE-84XM4EW18SS Manufacturer Page](#)

### SCE-84XM4EW18SS Notes

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for

IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

## SCE-84XM4EW18SS Application

Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

~~\$25,852.40~~ **\$14,270.52** You Save Today! (SCE-84XM4EW18SS)



## SCE-84XM4EW24SS 4DR SS XM Enclosure - 84" H X 157.5" W X 24" D

The SCE-84XM4EW24SS is a 84 x 157.5 x 18 4DR XM Enclosure from Saginaw Control & Engineering. Each SCE-84XM4EW24SS measures 84 Inches High X 157.5 Inches Wide X 18 Inches Deep. This SCE-84XM4EW24SS is Rated / Listed: NEMA 3R, NEMA 4, NEMA 4X, NEMA 12, NEMA 13, UL Listed Type 3R, UL Listed Type 4, UL Listed Type 4X, UL Listed Type 12, UL Listed Type 13, CSA Type 4, CSA Type 4X, CSA Type 12, IEC 60529, IP 66. Each Saginaw Control SCE-84XM4EW24SS 4DR XM Enclosure weighs 1850 lbs.

NOTE: Includes Quantity 2 [SCE-76P76](#) Bent Subpanels included with enclosure. Replacement plates can be ordered.

SCE-84XM4EW24SS 4DR XM Enclosure Application: Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

SCE-84XM4EW24SS Dimensions: 84 x 157.5 x 24

SCE-84XM4EW24SS Finish: 304 Stainless Steel. #4 brushed finish on all exterior surfaces. Sub-panels are powder coated white.

Notes: Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Because the SCE-84XM4EW24SS units are Made in the USA by Saginaw Control with 100% US components, the SCE-84XM4EW24SS from SCE meets all requirements of ARRA and Buy America. Every SCE-84XM4EW24SS has the highest quality and American craftsmanship built in.

Most of all, the SCE-84XM4EW24SS 4DR XM Enclosure comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-84XM4EW24SS 4DR XM Enclosure units are rated for NEMA 3R, 12, 13 environment and therefore have an Industry Standard of IS3. Each SCE-84XM4EW24SS 4DR XM Enclosure is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom 4DR SS XM Enclosure. If this 4DR SS XM Enclosure or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

## Recommended Accessory / Subpanel

[SCE-13ELJEXPP](#)

## Data Sheet

[SCE-84XM4EW24SS Datasheet / Cutsheet](#)

## Drawing / CAD Files

[SCE-84XM4EW24SS Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x\\_t files\)](#)

## Installation Information

[SCE-84XM4EW24SS Installation Information](#)

## Manufacturer Page

[SCE-84XM4EW24SS Manufacturer Page](#)

## SCE-84XM4EW24SS Notes

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

## SCE-84XM4EW24SS Application

Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects. SCE-84XM4EW24SS

~~\$27,044.22~~ **\$16,643.46** You Save Today! (SCE-84XM4EW24SS)



## SCE-90XM4EW18SS 4DR SS XM Enclosure - 90" H X 157.5" W X 18" D

The SCE-90XM4EW18SS is a 90 x 157.5 x 18 4DR XM Enclosure from Saginaw Control & Engineering. Each SCE-90XM4EW18SS measures 90 Inches High X 157.5 Inches Wide X 18 Inches Deep. This SCE-90XM4EW18SS is Rated / Listed: NEMA 3R, NEMA 4, NEMA 4X, NEMA 12, NEMA 13, UL Listed Type 3R, UL Listed Type 4, UL Listed Type 4X, UL Listed Type 12, CSA Type 4, CSA Type 4X, CSA Type 12, IEC 60529, IP 66. Each Saginaw Control SCE-90XM4EW18SS 4DR XM Enclosure weighs 2000 lbs.

SCE-90XM4EW18SS 4DR XM Enclosure Application: Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

SCE-90XM4EW18SS Dimensions: 90 x 157.5 x 18

SCE-90XM4EW18SS Finish: Type 304 Stainless Steel (T304). #4 brushed finish on all exterior surfaces. Subpanels are powder coated white.

Notes: Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Because the SCE-90XM4EW18SS units are Made in the USA by Saginaw Control with 100% US components, the SCE-90XM4EW18SS from SCE meets all requirements of ARRA and Buy America. Every SCE-90XM4EW18SS has the highest quality and American craftsmanship built in.

Most of all, the SCE-90XM4EW18SS 4DR XM Enclosure comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-90XM4EW18SS 4DR XM Enclosure units are rated for NEMA 3R, 12, 13 environment and therefore have an Industry Standard of IS3. Each SCE-90XM4EW18SS 4DR XM Enclosure is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom 4DR XM Enclosure. If this 4DR XM Enclosure or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

## Recommended Accessory / Subpanel

[SCE-13ELJEXPP](#)

## Data Sheet

[SCE-90XM4EW18SS Datasheet / Cutsheet](#)

## Drawing / CAD Files

[SCE-90XM4EW18SS Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x\\_t files\)](#)

## Installation Information

[SCE-90XM4EW18SS Installation Information](#)

## Manufacturer Page

[SCE-90XM4EW18SS Manufacturer Page](#)

## SCE-90XM4EW18SS Notes

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

## SCE-90XM4EW18SS Application

Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

~~\$26,944.43~~ **\$16,600.46** You Save Today! (SCE-90XM4EW18SS)

## SCE-90XM4EW24SS 4DR SS XM Enclosure - 90" H X 157.5" W X 24" D

The SCE-90XM4EW24SS is a 90 x 157.5 x 24 4DR XM Enclosure from Saginaw Control & Engineering. Each SCE-90XM4EW24SS measures 90 Inches High X 157.5 Inches Wide X 24 Inches Deep. This SCE-90XM4EW24SS is Rated / Listed: NEMA 3R, NEMA 12, NEMA 13, UL Listed Type 3R, UL Listed Type 12, CSA Type 3R, CSA Type 12, IEC 60529, IP 55. Each Saginaw Control SCE-90XM4EW24SS 4DR XM Enclosure weighs 2030 lbs.

SCE-90XM4EW24SS 4DR XM Enclosure Application: Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

SCE-90XM4EW24SS Dimensions: 90 x 157.5 x 24

SCE-90XM4EW24SS Finish: 304 Stainless Steel (T304). #4 brushed finish on all exterior surfaces. Sub-panels are powder coated white.

Notes: Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Because the SCE-90XM4EW24SS units are Made in the USA by Saginaw Control with 100% US components, the SCE-90XM4EW24SS from SCE meets all requirements of ARRA and Buy America. Every SCE-90XM4EW24SS has the highest quality and American craftsmanship built in.

Most of all, the SCE-90XM4EW24SS 4DR XM Enclosure comes with an industry leading SCE manufacturer two year (2 year) warranty. All SCE-90XM4EW24SS 4DR XM Enclosure units are rated for NEMA 3R, 12, 13 environment and therefore have an Industry Standard of IS3. Each SCE-90XM4EW24SS 4DR XM Enclosure is precision manufactured by Saginaw Control & Engineering, an ISO 9001:2015 registered company, with state of the art precision fabricating equipment including the latest in laser technology, stainless steel process and powder coat finishes.

Custom 4DR XM Enclosure. If this 4DR XM Enclosure or other catalog items aren't exactly what you need, ATG and Saginaw Control can help. We will provide your custom enclosure to your exact specification with industry leading turnaround and pricing. Get a Quick Quote Above.

## Recommended Accessory / Subpanel

[SCE-13ELJEXPP](#)

## Data Sheet

[SCE-90XM4EW24SS Datasheet / Cutsheet](#)

## Drawing / CAD Files

[SCE-90XM4EW24SS Drawing / CAD Package \(.zip includes pdf, dwg, igs, stp, x\\_t files\)](#)

## Installation Information

[SCE-90XM4EW24SS Cutler Hammer Installation Information](#)  
[SCE-90XM4EW24SS Moller Installation Information](#)  
[SCE-90XM4EW24SS ABB Installation Information](#)



[GE Installation Information](#)  
[Siemens Installation Information](#)  
[Allen-Bradley Installation Information](#)  
[Bussman Installation Information](#)  
[Gould Installation Information](#)  
[Square D Installation Information](#)  
[SCE-90XM4EW24SS Additional Installation Information](#)  
[SCE-90XM4EW24SS Additional Installation Information](#)  
[Lighting Installation Information](#)  
[SCE-90XM4EW24SS Additional Installation Information](#)  
[SCE-90XM4EW24SS Additional Installation Information](#)  
[Vent Installation Information](#)  
[Bolt In Barrier Installation Information](#)  
[SCE-90XM4EW24SS Installation Information](#)

## Manufacturer Page

[SCE-90XM4EW24SS Manufacturer Page](#)

## SCE-90XM4EW24SS Notes

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure. SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect. Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

## SCE-90XM4EW24SS Application

Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

~~\$27,982.42~~ **\$17,239.97 You Save Today!** (SCE-90XM4EW24SS)