



Your Enclosure Source®

Saginaw Control & Engineering
95 Midland Road
Saginaw, MI 48638-5770
Phone: (800)234-6871
Fax: (989)799-4524
<http://www.saginawcontrol.com>

Part Information - SCE-60XEL6124LP

→ SCE-60XEL6124LP

Application -

Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects.

Construction -

- 0.104" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Oil-resistant gasket.
- Concealed hinge.
- Removable and interchangeable doors.
- 3-point latching mechanism.
- Removable print pocket.
- Lifting eyes for easy handling.
- Ground studs on door and body.
- Collar studs provided for mounting optional panels.
- 15" removable floor stand.
- Removable center post.
- Mechanical interlock.
- No door stiffeners required.
- Black zinc die cast coinproof/padlocking handle on main door of disconnect enclosures. Black zinc die cast padlocking handle on all other doors.
- Provisions for light kit.

Finish -

ANSI-61 gray powder coating inside and out. Optional sub-panels are powder coated white.

Industry Standards - (IS4)

NEMA Type 3R, 4, 12 and Type 13
UL Listed Type 3R, 4 and 12
CSA Type 3R, 4 and 12
IEC 60529 IP 66

Notes -

Disconnect switch (or circuit breaker and operating mechanism) are not furnished with this enclosure.

SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Product Specifications -

Part Number: SCE-60XEL6124LP
Description: 2DR XEL Enclosure
Height: 60.00"
Width: 61.00"
Depth: 24.00"
Price Code: A2
List Price: \$2,823.42
Catalog Page: 134
Est. Ship Weight: 650.00 lbs



[Download CAD Package](#)
[Add to Bill of Material](#)

Optional Accessories -

[SCE-13ELJEXPP](#) - Pocket, Exterior Print
[SCE-19ELJEXPP](#) - Pocket, Exterior Print
[SCE-60P60](#) - Subpanel, Bent
[SCE-BP5624](#) - Plate, Barrier
[SCE-BV4XKIT](#) - Kit, Breather Vent
[SCE-DF60EL60](#) - Panel, Dead Front (Enviroline Floor Mount)
[SCE-DS60N4](#) - Shield, Drip
[SCE-DV4XKIT](#) - Kit, Drain Vent
[SCE-FS1212](#) - Shelf, Folding
[SCE-FS1818](#) - Shelf, Folding
[SCE-FS2424](#) - Shelf, Folding
[SCE-LF18](#) - Fixture, LED Light
[SCE-LF18NO](#) - Fixture, LED Light w/o Outlet

Similar Part Numbers -

[SCE-60XEL4912LP](#) - 2DR XEL Enclosure
[SCE-60XEL4918LP](#) - 2DR XEL Enclosure
[SCE-60XEL4924LP](#) - 2DR XEL Enclosure
[SCE-60XEL6112LP](#) - 2DR XEL Enclosure
[SCE-60XEL6118LP](#) - 2DR XEL Enclosure
[SCE-72XEL6112LP](#) - 2DR XEL Enclosure
[SCE-72XEL6118LP](#) - 2DR XEL Enclosure
[SCE-72X7312LP](#) - 2DR X LP Enclosure
[SCE-72X7318LP](#) - 2DR X LP Enclosure
[SCE-72X7324LP](#) - 2DR X LP Enclosure

Installation Information -

[Mechanical Defeater \(Cable Operated\)](#)
[Mechanical Defeater \(Variable Depth\)](#)
[Square D Flange Mounted, Disconnects and Circuit Breakers](#)
[Gould Flange Mounted, Disconnects and Circuit Breakers](#)
[Bussmann Flange Mounted, Disconnects and Circuit Breakers](#)
[Allen-Bradley Flange Mounted, Disconnects and Circuit Breakers](#)
[Siemens Flange Mounted, Disconnects and Circuit Breakers](#)
[GE Flange Mounted, Disconnects and Circuit Breakers](#)

[ABB Flange Mounted, Disconnects and Circuit Breakers](#)
[Moller Flange Mounted, Disconnects and Circuit Breakers](#)
[Cutler-Hammer Flange Mounted, Disconnects and Circuit Breakers](#)
[LED Light Fixture](#)
[Drain/Vents](#)
[Drip Shield Kit Assembly](#)

Drift Shield Kit Assembly

Folding Shelf Hole Pattern

Dead Front 2 Door W/Disconnect Installation Instructions

Saginaw Control and Engineering
95 Midland Road
Saginaw, MI 48638-5770
(800)234-6871
Fax: (989)799-4524
SCE@SaginawControl.com