



Your Enclosure Source®

Saginaw Control & Engineering
95 Midland Road
Saginaw, MI 48638-5770
Phone: (800)234-6871
Fax: (989)799-4524
<http://www.saginawcontrol.com>

Part Information - SCE-72XEL7312SS6LP

→ SCE-72XEL7312SS6LP

Application -

Designed to house electrical and electronic controls, instrumentation and components in indoor & outdoor locations. Designed to house most standard type disconnects. For outdoor application a drip shield is recommended.

Construction -

- 0.104" stainless steel Type 316/316L.
- Seams continuously welded and ground smooth.
- Oil-resistant gasket.
- Flange trough collar around all sides of door opening.
- Stainless steel concealed hinge.
- Removable and interchangeable doors.
- 3-point latching mechanism.
- Removable print pocket.
- Lifting eyes for easy handling.
- Ground studs on door and body.
- Collar studs provided for mounting optional panels.
- 15" removable floor stands.
- Removable center post.
- Mechanical interlock.
- No door stiffeners required.
- Black zinc die cast coinproof/padlocking handle on main door of disconnect enclosures. Black zinc die cast padlocking handle on all other doors.
- Provisions for light kit.

Finish -

#4 brushed finish on all exterior surfaces.
Optional sub-panels are powder coated white.

Industry Standards - (IS6)

NEMA Type 3R, 4, 4X, 12 and Type 13
UL Listed Type 3R, 4, 4X and 12
CSA Type 4, 4X and 12
IEC 60529 IP 66

Notes -

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure.

SCE-125738 Defeater kit is required for use with Mechanical Defeater when using Siemens and ABB Flange mount Disconnect.

Product Specifications -

Part Number: SCE-72XEL7312SS6LP
Description: S.S. 2DR XEL Enclosure
Height: 72.00"
Width: 73.00"
Depth: 12.00"
Price Code: S7
List Price: \$13,366.23
Catalog Page: 252
Est. Ship Weight: 730.00 lbs



[Download CAD Package](#)
[Add to Bill of Material](#)

Optional Accessories -

[SCE-13ELJEXPP](#) - Pocket, Exterior Print
[SCE-19ELJEXPP](#) - Pocket, Exterior Print
[SCE-72P72](#) - Subpanel, Bent
[SCE-BP6812](#) - Plate, Barrier
[SCE-BV4XKIT](#) - Kit, Breather Vent
[SCE-DF72EL72](#) - Panel, Dead Front (Enviroline Floor Mount)
[SCE-DS60SS](#) - Shield, S.S. Drip
[SCE-DV4XKIT](#) - Kit, Drain Vent
[SCE-FS1212SS](#) - Shelf, S.S. Folding
[SCE-FS1818SS](#) - Shelf, S.S. Folding
[SCE-FS2424SS](#) - Shelf, S.S. Folding
[SCE-LF18](#) - Fixture, LED Light
[SCE-LF18NO](#) - Fixture, LED Light w/o Outlet
[SCE-LF24](#) - Fixture, LED Light
[SCE-LF24NO](#) - Fixture, LED Light w/o Outlet

Similar Part Numbers -

[SCE-60XEL6112SS6LP](#) - S.S. 2DR XEL Enclosure
[SCE-60XEL6118SS6LP](#) - S.S. 2DR XEL Enclosure
[SCE-72XEL6112SS6LP](#) - S.S. 2DR XEL Enclosure
[SCE-72XEL6118SS6LP](#) - S.S. 2DR XEL Enclosure
[SCE-72XEL7318SS6LP](#) - S.S. 2DR XEL Enclosure
[SCE-72XEL7324SS6LP](#) - S.S. 2DR XEL Enclosure

Installation Information -

[Mechanical Defeater \(Variable Depth\)](#)
[Gould Flange Mounted, Disconnects and Circuit Breakers](#)
[Square D Flange Mounted, Disconnects and Circuit Breakers](#)
[Mechanical Defeater \(Cable Operated\)](#)
[Cutler-Hammer Flange Mounted, Disconnects and Circuit Breakers](#)
[Allen-Bradley Flange Mounted, Disconnects and Circuit Breakers](#)
[Bussmann Flange Mounted, Disconnects and Circuit Breakers](#)
[ABB Flange Mounted, Disconnects and Circuit Breakers](#)
[GE Flange Mounted, Disconnects and Circuit Breakers](#)
[Moller Flange Mounted, Disconnects and Circuit Breakers](#)

[Siemens Flange Mounted, Disconnects and Circuit Breakers](#)
[Drain/Vents](#)
[Drip Shield Kit Assembly](#)
[Folding Shelf Hole Pattern](#)
[Dead Front 2 Door W/Disconnect Installation Instructions](#)

Saginaw Control and Engineering
95 Midland Road
Saginaw, MI 48638-5770
(800)234-6871
Fax: (989)799-4524
SCE@SaginawControl.com